reverie oak

Comfort | CC0803

Reducer

WP01060_00003RD



0.708 in.

Used to transition between two flooring heights, providing a smooth change.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.39

TRIM WIDTH (in.)

1.77



T-Mold

WP01060_00003TM



Covers the seam between two floors of equal height.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.39

TRIM WIDTH (in.)

1.71



Quarter Round

WP01060_00003QR

Installed along the base of the wall to cover gaps and add a decorative touch.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.708

TRIM WIDTH (in.)

0.708



4.5 in.

Threshold

WP01060_00003BT

1.73 in.

2.01 in.

Creates a smooth transition between rooms or doorways, often at entryways.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.35

TRIM WIDTH (in.)

1.73



Flush Stair Nose

WP01060_00003FS

Provides a clean, flush edge where the stair nose meets the floor. $\,$

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

1.57

TRIM WIDTH (in.)

4.5



Overlap Stair Nose

WP01060_00003OS

Covers the edge of the stair, overlapping the flooring of the step.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

1.5

TRIM WIDTH (in.)

2.01



reverie oak



4.49 in.

Comfort | CC0803

Riser

INCLUDED WITH STAIR TREADS

12.2 in.

The vertical piece between the stair steps.

TRIM LENGTH (in.) 44.09

TRIM THICKNESS (in.)

.15

TRIM WIDTH (in.)

7.48



Stair Tread



TRIM LENGTH (in.)

50

TRIM HEIGHT (in.)

1.73

TRIM WIDTH (in.)

12.2



Square Stair Tread

WP01060_00003SQST

The horizontal surface of the stair, covering the entire

stepping area with a square-edged nose.

TRIM LENGTH (in.)

50

TRIM HEIGHT (in.)

1.73

TRIM WIDTH (in.)

12.2



Flush Square Stair Nose

WP01060_00003FSQ

Provides a clean, flush edge where the square-edged stair nose meets the floor

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

1.73

TRIM WIDTH (in.)

4.49



Stair Treads Tip: Complete the look on the top stair with a flush or overlap stair nose.