harbor oak



Comfort Premium | CC1506

Reducer

WP1584_00006RD

2.17 in.

0.708 in.

Used to transition between two flooring heights, providing a smooth change.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.69

TRIM WIDTH (in.)

2.17



T-Mold

WP1584_00006TM



Covers the seam between two floors of equal height.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.59

TRIM WIDTH (in.)

1.71



Quarter Round

WP1584_00006QR

Installed along the base of the wall to cover gaps and add a decorative touch.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.708

TRIM WIDTH (in.)

0.708



4.5 in.

Threshold

WP1584_00006BT



2.01 in.

Creates a smooth transition between rooms or doorways, often at entryways.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.69

TRIM WIDTH (in.)

1.73



Flush Stair Nose

WP1584_00006FS

Provides a clean, flush edge where the stair nose meets the floor. $\,$

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

1.57

TRIM WIDTH (in.)

4.5



Overlap Stair Nose

WP1584_00006OS

Covers the edge of the stair, overlapping the flooring of the step.

TRIM LENGTH (in.) **94.5**

TRIM HEIGHT (in.)

1.5

TRIM WIDTH (in.)

2.01



harbor oak



Comfort Premium | CC1506





Stair Treads Tip: Complete the look on the top stair with a flush or overlap stair nose.