latte oak



Comfort Premium | CC1512

Reducer

WP1584_00012RD

2.17 in.

0.708 in.

Used to transition between two flooring heights, providing a smooth change.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.69

TRIM WIDTH (in.)

2.17



T-Mold

WP1584_00012TM



Covers the seam between two floors of equal height.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.59

TRIM WIDTH (in.)

1.71



Quarter Round

WP1584_00012QR

Installed along the base of the wall to cover gaps and add a decorative touch.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.708

TRIM WIDTH (in.)

0.708



4.5 in.

Threshold

WP1584_00012BT



2.01 in.

Creates a smooth transition between rooms or doorways, often at entryways.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.69

TRIM WIDTH (in.)

1.73



Flush Stair Nose

WP1584_00012FS



TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

1.57

TRIM WIDTH (in.)

4.5



Overlap Stair Nose

WP1584_00012OS

Covers the edge of the stair, overlapping the flooring of the step.



94.5

TRIM HEIGHT (in.)

1.5

TRIM WIDTH (in.)

2.01



latte oak



Comfort Premium | CC1512

Riser

INCLUDED WITH STAIR TREADS

12.2 in.

The vertical piece between the stair steps.

TRIM LENGTH (in.) 44.09

TRIM THICKNESS (in.)

TRIM WIDTH (in.)


7.48

.15



Stair Tread

WP1584_00012ST



The horizontal surface of the stair, covering the entire stepping area.

TRIM LENGTH (in.)

50

TRIM HEIGHT (in.)

1.73

TRIM WIDTH (in.)

12.2



Square Stair Tread

WP1584_00012SQST

The horizontal surface of the stair, covering the entire

Flush Square Stair Nose

WP1584_00012FSQ

4.49 in. Provides a clean, flush edge where the square-edged

stepping area with a square-edged nose.

TRIM LENGTH (in.)

50

TRIM HEIGHT (in.)

1.73

TRIM WIDTH (in.)

12.2



TRIM LENGTH (in.) 94.5

stair nose meets the floor

TRIM HEIGHT (in.)

1.73

TRIM WIDTH (in.)

4.49



Stair Treads Tip: Complete the look on the top stair with a flush or overlap stair nose.