

CANYON SELECT XL

Built Stronger to Last Longer

IFC



MATERIAL

BEVEL

Micro Bevel

WEAR

0.50 mm (20 mil)

FINISH

UV Coating - Scratch and Fade Resistant

INSTALLATION

Floating or Direct Glue

CONSTRUCTION

Stone Polymer Core LVP

PAD TYPE

Attached cork pad for added comfort

PROFILE TYPE

DIY Friendly Click

EMBOSSING

Standard

SIZE

THICKNESS

6 mm (1/4 in)

CORE THICKNESS

5 mm (3/16 in)

PAD THICKNESS

1 mm (1/32 in)

GUARANTEES

CERTIFICATIONS

Greenguard Gold

WARRANTY

Lim. Lifetime / 15 Yr. Med. Commercial

PACKAGING

SF / CARTON

26.95 sq. ft / carton

EACHES / CARTON

6 planks / carton

WEIGHT / CARTON

58.43 lbs / carton

CARTONS / PALLET

56 cartons / pallet

SF / PALLET

1509.20 sf / pallet

6FT

9"



Limited lifetime warranty



Greenguard certified



100% waterproof



DIY friendly

IFC
INTERNATIONAL
FLOORING CO
A DOSSCHE FAMILY COMPANY

PRODUCTS



Hampton Oak
SP0672_00001



Colonial Oak
SP0672_00002



Sullivans Oak
SP0672_00003



Sumnter Oak
SP0672_00004



Post Oak
SP0672_00005

MATCHING TRIMS AVAILABLE



T - Mold



Reducer



Threshold



Stair Nose



Overlap Stair Nose



Quarter Round