dawn oak

Comfort NE+ | CC0825

Reducer

WP0860_00025RD



0.708 in.

Used to transition between two flooring heights, providing a smooth change.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.39

TRIM WIDTH (in.)

1.77



T-Mold

WP0860_00025TM



Covers the seam between two floors of equal height.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.39

TRIM WIDTH (in.)

1.71



Quarter Round

WP0860_00025QR

Installed along the base of the wall to cover gaps and add a decorative touch.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.708

TRIM WIDTH (in.)

0.708



4.5 in.

Threshold

WP0860_00025BT



2.01 in.

Creates a smooth transition between rooms or doorways, often at entryways.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.35

TRIM WIDTH (in.)

1.73



Flush Stair Nose

WP0860_00025FS



TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

1.57

TRIM WIDTH (in.)

4.5



Overlap Stair Nose

WP0860_00025OS

Covers the edge of the stair, overlapping the flooring of the step.



94.5

TRIM HEIGHT (in.)

1.5

TRIM WIDTH (in.)

2.01



dawn oak



Comfort NE+ | CC0825

Riser

INCLUDED WITH STAIR TREADS

7.48

The vertical piece between the stair steps.

TRIM LENGTH (in.) 44.09

TRIM THICKNESS (in.)

TRIM WIDTH (in.)

7.48


.15



12.2 in.

Stair Tread

WP0860_00025ST



The horizontal surface of the stair, covering the entire stepping area.

TRIM LENGTH (in.)

50

TRIM HEIGHT (in.)

1.73

TRIM WIDTH (in.)

12.2



Square Stair Tread

WP0860_00025SQST

The horizontal surface of the stair, covering the entire stepping area with a square-edged nose.

Flush Square Stair Nose

WP0860_00025FSQ

Provides a clean, flush edge where the square-edged stair nose meets the floor

4.49 in.

TRIM LENGTH (in.)

50

TRIM HEIGHT (in.)

1.5

TRIM WIDTH (in.)

12.2



TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

1.73

TRIM WIDTH (in.)

4.49



Stair Treads Tip: Complete the look on the top stair with a flush or overlap stair nose.