## saddle oak



Comfort Premium | CC1514

#### Reducer

WP1584\_00014RD

2.17 in.

0.708 in.

Used to transition between two flooring heights, providing a smooth change.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.69

TRIM WIDTH (in.)

2.17



#### T-Mold

WP1584\_00014TM



Covers the seam between two floors of equal height.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.59

TRIM WIDTH (in.)

1.71



#### Quarter Round

WP1584\_00014QR

Installed along the base of the wall to cover gaps and add a decorative touch.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.708

TRIM WIDTH (in.)

0.708



4.5 in.

#### Threshold

WP1584\_00014BT



2.01 in.

Creates a smooth transition between rooms or doorways, often at entryways.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.69

TRIM WIDTH (in.)

1.73



#### Flush Stair Nose

WP1584\_00014FS

Provides a clean, flush edge where the stair nose meets the floor.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

1.57

TRIM WIDTH (in.)

4.5



### Overlap Stair Nose

WP1584\_00014OS

Covers the edge of the stair, overlapping the flooring of the step.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

1.5

TRIM WIDTH (in.)

2.01



# saddle oak



Comfort Premium | CC1514





Stair Treads Tip: Complete the look on the top stair with a flush or overlap stair nose.